





D 向



Laifual Drive

Technical Requirements:

1.Please use the grease specified by our company (LF-2 or F-3).
2.The * in the drawing is the installation reference size, please follow the installation size requirements.
3.For details of size, please confirm with the delivery specification drawings.

LSG-32-XX-U-I

MODEL	U	T	W
Wave generator-A φ14	φ14H7	$16.3^{+0.1}_{0}$	5JS9/P9
Wave generator-A φ19	φ19H7	$21.8^{+0.1}_{0}$	6JS9/P9
Wave generator-A φ22	φ22H7	$24.8^{+0.1}_{0}$	6JS9/P9
		$25.3^{+0.1}_{0}$	8JS9/P9

Model	Reduction ratio	Rated torque at 2000r/min input		Permissible peak torque at start and stop		Permissible maximum value for average load		Permissible maximum momentary torque		Permissible maximum input rotational speed (Grease)	Permissible average input rotational speed (Greaae)	Backlash	weight	Desian life
		Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min	r/min	Arc Sec	kg	Hour
32	50	99	10	281	29	140	14	497	51	4800	3500	⩽20	LSG-I:3.11	15000
	80	153	16	395	40	217	22	738	75					15000
	100	178	18	433	44	281	29	841	86					15000
	120	178	18	459	47	281	29	892	91					15000